

## General information

AUMA NORM multi-turn actuators require electric controls. For the SAREx type range, AUMA offers AMExC and ACExC actuator controls. These can also easily be mounted to the actuator at a later date.

Type	Output speed rpm		Torque range <sup>1)</sup>		Modulating torque <sup>2)</sup>	Number of starts <sup>3)</sup>	Pulse duration <sup>4)</sup>		Valve attachment <sup>6)</sup>			Handwheel		Weight <sup>7)</sup>
	50 Hz	60 Hz	Min. [Nm]	Max. [Nm]	Max. [Nm]	Starts Max. [1/h]	Min. [ms]	Max. [ms]	Standard EN ISO 5210	Option DIN 3210	Max. Ø rising stem [mm]	Ø [mm]	Reduction ratio	approx. [kg]
SAREx 07.2	4	4.8	15	30	15	600	50	260	F07 F10	– G0	26 34	160	11 : 1	28
	5.6	6.7						200					8 : 1	
	8	9.6						155					11 : 1	
	11	13						130					8 : 1	
	16	19						100					11 : 1	
	22	26						90					8 : 1	
	32	38						75					11 : 1	31
	45	54						70					8 : 1	
SAREx 07.6	4	4.8	30	60	30	600	50	260	F07 F10	– G0	26 34	160	11 : 1	28
	5.6	6.7						200					8 : 1	
	8	9.6						155					11 : 1	
	11	13						130					8 : 1	
	16	19						100					11 : 1	
	22	26						90					8 : 1	
	32	38						75					11 : 1	31
	45	54						70					8 : 1	
SAREx 10.2	4	4.8	60	120	60	600	50	260	F10	G0	40	200	11 : 1	32
	5.6	6.7						200					8 : 1	
	8	9.6						155					11 : 1	35
	11	13						130					8 : 1	
	16	19						100					11 : 1	
	22	26						90					8 : 1	
SAREx 14.2	4	4.8	120	250	120	600	70	280	F14	G1/2	58	315	11 : 1	63
	5.6	6.7						220					8 : 1	
	8	9.6						175					11 : 1	
	11	13						150					8 : 1	
SAREx 14.6	4	4.8	250	500	200	600	70	280	F14	G1/2	58	400	11 : 1	67
	5.6	6.7						220					8 : 1	

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
- 2) Maximum permissible torque for modulating duty.
- 3) An off-time (reversing prevention time) of minimum 2.5 seconds is required prior to starting in opposite direction.
- 4) For identical direction of rotation: Time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 5) For reversal of rotation direction: Time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 6) Indicated flange sizes apply for output drive types A and B1. Refer to separate dimension sheets for further output drive types.
- 7) Indicated weight includes AUMA NORM multi-turn actuator with 1-phase AC motor, electrical connection in standard version, output drive type B1 and handwheel.

## Features and functions

Explosion protection	Standard:	II 2G Ex db eb IIB T4 or T3 Gb II 2G Ex h IIB T4 or T3 Gb II 2D Ex tb IIIC T130°C or T190°C Db
	Options:	II 2G Ex db IIB T4 or T3 Gb II 2G Ex h IIB T4 or T3 Gb
Product certificates	DEKRA 11ATEX0008 X	
Type of duty	Intermittent duty S4 - 25 %, class C according to EN ISO 22153 For nominal voltage and +40 °C ambient temperature and at modulating torque load.	
Motors	1-phase AC motor with integral permanent split capacitor (PSC), type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6	

Features and functions	
Mains voltage, mains frequency	Standard voltages: Refer to table: <a href="#">1-phase AC standard voltages [► 2]</a> Further voltages on request Permissible variation of mains voltage: $\pm 10\%$ Permissible variation of mains frequency: $\pm 5\%$
Overvoltage category	Category III according to IEC 60364-4-44
Insulation class	F, tropicalized
Motor protection	PTC thermistors (according to DIN 44082) PTC thermistors additionally require a suitable tripping device in the actuator controls
Self-locking	Yes (actuators are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.)
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC Power 12.5 W
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation. Options: Handwheel lockable Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm
Indication for manual operation (option)	Indication whether manual operation is active/not active via single switch (1 change-over contact)
Electrical connection	Standard: AUMA Ex plug/socket connector (KT); screw-type motor terminals; control terminals in spring clamp terminal technology Option: AUMA Ex plug/socket connector with terminal blocks (KES)
Threads for cable entries	Standard: Metric threads Option: Pg threads, NPT threads, G threads
Wiring diagram	TPA01R2AA-001-000 (basic version) TPA01R2AA-101-000, 1-phase AC motor with permanent split capacitor 100 – 240 V AC (basic version in combination with PTC thermistors)
Valve attachment	Standard: B1 in accordance with ISO 5210 Options: A, B2, B3, B4, C, D according to ISO 5210 A, B, D, E according to DIN 3210 C according to DIN 3338 Special valve attachments: AF, AK, AG, B3D, ED, DD, IB1, IB3 A prepared for permanent lubrication of stem

Table 1: 1-phase AC standard voltages

Voltages/frequencies				
Volt [1~]	110 – 120	110 – 120	220 – 240	220 – 240
Hz	50	60	50	60

Electromechanical control unit	
Limit switching	Counter gear mechanism for end positions OPEN and CLOSED Turns per stroke: 2 to 500 (standard) or 2 to 5,000 (option) Standard: Single switch (1 NC and 1 NO) for each end position, not galvanically isolated Options: Tandem switch (2 NC and 2 NO) for each end position, switch galvanically isolated Triple switch (3 NC and 3 NO) for each end position, switch galvanically isolated Intermediate position switches (DUO limit switching), adjustable for each direction of operation
Torque switching	Torque switching adjustable for directions OPEN and CLOSE Standard: Single switch (1 NC and 1 NO) for each direction, not galvanically isolated Option: Tandem switch (2 NC and 2 NO) for each direction, switch galvanically isolated
Switch contact materials	Standard: Silver (Ag) Option: Gold (Au), recommended for low voltage actuator controls
Position feedback signal, analogue (options)	Potentiometer or 0/4 – 20mA (electronic position transmitter)
Mechanical position indicator (option)	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED
Running indication (option)	Blinker transmitter

Electromechanical control unit		
Heater in switch compartment	Standard:	Self-regulating PTC heater, 5 – 20 W, 110 – 250 V AC/DC
	Options:	24 – 48 V AC/DC
	A resistance type heater of 5 W, 24 V AC is installed in the actuator in combination with AMExC or ACExC actuator controls.	
Electronic control unit (option, only in combination with ACExC actuator controls)		
Non-intrusive settings	Magnetic limit and torque transmitter (MWG) Turns per stroke: 2 to 500 (standard) or 10 to 5,000 (option)	
Position feedback signal	Via actuator controls	
Torque feedback signal	Via actuator controls	
Mechanical position indicator (option)	Continuous self-adjusting indication with symbols OPEN and CLOSED	
Running indication	Blinking signal via actuator controls	
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC	
Service conditions		
Use	Indoor and outdoor use permissible	
Mounting position	Any position	
Installation altitude	≤ 2,000 m above sea level	
	> 2,000 m above sea level on request	
Ambient temperature	Standard:	–30 °C to +40 °C/+60 °C
	Options:	–40 °C to +40 °C/+60 °C
		–50 °C to +40 °C/+60 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range	
Enclosure protection in accordance with IEC 60529	IP68 with AUMA 1-phase AC motors of types AE..., VE...	
	Terminal compartment additionally sealed against interior of actuator (double sealed)	
	According to AUMA definition, enclosure protection IP68 meets the following requirements:	
	<ul style="list-style-type: none"><li>• Depth of water: maximum 8 m head of water</li><li>• Continuous immersion in water: maximum 96 hours</li><li>• Up to 10 operations during immersion</li><li>• Modulating duty is not possible during immersion.</li></ul>	
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)	
Corrosion protection	Standard:	KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution.
	Option:	KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution.
Coating	Double layer powder coating	
Coating	Double layer powder coating	
Colour	Standard:	AUMA silver-grey (similar to RAL 7037)
	Option:	Available colours on request
Lifetime	AUMA multi-turn actuators meet or exceed the lifetime requirements of EN ISO 22153. Detailed information can be provided on request.	
Sound pressure level	< 72 dB (A)	
Further information		
EU Directives	ATEX Directive 2014/34/EU Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU	
Reference documents	Dimensions SAEx 07.2 – SAEx 16.2/SAREx 07.2 – SAREx 16.2 Electrical data SAREx 07.2 – SAREx 16.2	