

General information

AUMA NORM multi-turn actuators require electric controls. For the SAREx type range, AUMA offers AMExC and ACExC actuator controls. These can also easily be mounted to the actuator at a later date.

Type	Output speed rpm		Torque range ¹⁾			Modulating torque ²⁾		Number of starts	Pulse duration ³⁾	Pulse duration on reversal ⁴⁾	Valve attachment ⁵⁾			Handwheel		Weight ⁶⁾
	50 Hz	60 Hz	Min. [Nm]	S4-25% Max. [Nm]	S4-50% Max. [Nm]	S4-25% Max. [Nm]	S4-50% Max. [Nm]				Starts Max. [1/h]	Min. [ms]	Max. [ms]	Standard EN ISO 5210	Option DIN 3210	
SAREx 07.2	4	4.8	15	30	20	15	8	1,200	50	260	F07 F10	– G0	26 34	160	11 : 1	22
	5.6	6.7								200					8 : 1	
	8	9.6								155					11 : 1	
	11	13								130					8 : 1	
	16	19								100					11 : 1	
	22	26								90					8 : 1	
	32	38								75					11 : 1	
	45	54								70					8 : 1	
	63	75						900		65					11 : 1	23
	90	108								60					8 : 1	
SAREx 07.6	4	4.8	30	60	40	30	15	1,200	50	260	F07 F10	– G0	26 34	160	11 : 1	22
	5.6	6.7								200					8 : 1	
	8	9.6								155					11 : 1	
	11	13								130					8 : 1	
	16	19								100					11 : 1	
	22	26								90					8 : 1	
	32	38								75					11 : 1	24
	45	54								70					8 : 1	
	63	75				20	10	900		65					11 : 1	
	90	108								60					8 : 1	
SAREx 10.2	4	4.8	60	120	90	60	30	1,000	50	260	F10	G0	40	200	11 : 1	26
	5.6	6.7								200					8 : 1	
	8	9.6								155					11 : 1	
	11	13								130					8 : 1	
	16	19								100					11 : 1	
	22	26								90					8 : 1	
	32	38								75					11 : 1	28
	45	54								70					8 : 1	
	63	75				50	25	800		65					11 : 1	
	90	108								60					8 : 1	
SAREx 14.2	4	4.8	120	250	180	120	60	900	70	280	F14	G1/2	58	315	11 : 1	48
	5.6	6.7								220					8 : 1	
	8	9.6								175					11 : 1	
	11	13								150					8 : 1	
	16	19						600		120					11 : 1	52
	22	26								110					8 : 1	
	32	38						300		100					11 : 1	
	45	54								90					8 : 1	
	63	75				100	50	200		85					11 : 1	
	90	108								80					8 : 1	
SAREx 14.6	4	4.8	250	500	360	200	100	900	70	280	F14	G1/2	58	400	11 : 1	50
	5.6	6.7								220					8 : 1	
	8	9.6								175					11 : 1	
	11	13								150					8 : 1	
	16	19						600		120					11 : 1	56
	22	26								110					8 : 1	
	32	38				150	75	300		100					11 : 1	
	45	54								90					8 : 1	
	63	75				120	60	200		85					11 : 1	
	90	108								80					8 : 1	

Type	Output speed rpm		Torque range ¹⁾			Modulating torque ²⁾		Num- ber of starts	Pulse dura- tion ³⁾	Pulse duration on re- versal ⁴⁾	Valve attachment ⁵⁾			Handwheel		Weight ⁶⁾
				S4-25%	S4-50%	S4-25%	S4-50%				Stand- ard EN ISO 5210	Option DIN 3210	Max. Ø rising stem			
	50 Hz	60 Hz	Min. [Nm]	Max. [Nm]	Max. [Nm]	Max. [Nm]	Max. [Nm]	Starts Max. [1/h]	Min. [ms]	Max. [ms]				Ø [mm]	Reduc- tion ra- tio	approx. [kg]
SAREx 16.2	4	4.8	500	1,000	710	400	200	600	100	300	F16	G3	77	500	11 : 1	72
	5.6	6.7								250					8 : 1	
	8	9.6				350	175	200		11 : 1						
	11	13						175		8 : 1						
	16	19				300	150	300		150					11 : 1	83
	22	26								140					8 : 1	
	32	38				250	125	200		130					11 : 1	
	45	54								120					8 : 1	
	63	75				200	100	150		115					11 : 1	88
	90	108								110					8 : 1	

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
- 2) Maximum permissible torque for modulating duty.
- 3) For identical direction of rotation: Time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 4) For reversal of rotation direction: Time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 5) Indicated flange sizes apply for output drive types A and B1. Refer to separate dimension sheets for further output drive types.
- 6) Indicated weight includes AUMA NORM multi-turn actuator with 3-phase AC motor, electrical connection in standard version, output drive type B1 and handwheel.

Features and functions

Explosion protection	Standard:	II 2G Ex db eb IIC T4 or T3 Gb II 2G Ex h IIC T4 or T3 Gb II 2D Ex tb IIIC T130°C or T190°C Db
	Options	II 2G Ex db IIC T4 or T3 Gb II 2G Ex h IIC T4 or T3 Gb
Product certificates	DEKRA 11ATEX0008 X	
Type of duty	Standard:	Intermittent duty S4 - 25 %, class C according to EN ISO 22153
	Option:	Intermittent duty S4 - 50 %, class C according to EN ISO 22153 Intermittent duty S5 - 25 % (insulation class H required), class C according to EN ISO 22153
	For nominal voltage and +40 °C ambient temperature and at modulating torque load.	
Motors	3-phase AC asynchronous squirrel-cage motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6	
Mains voltage, mains frequency	Standard voltages:	
	Refer to table: 3-phase AC standard voltages [► 3]	
	Special voltages:	
	Refer to table: 3-phase AC special voltages [► 3]	
	Further voltages on request	
Overvoltage category	Category III according to IEC 60364-4-443	
	Standard:	F, tropicalized
Insulation class	Option:	H, tropicalized
Motor protection	PTC thermistors (according to DIN 44082)	
	PTC thermistors additionally require a suitable tripping device in the actuator controls	
Self-locking	Yes (actuator are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.)	
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC	
	Power depending on the size 12.5 W	
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation.	
	Options:	Handwheel lockable Handwheel stem extension
	Power tool for emergency operation with square 30 mm or 50 mm	

Features and functions	
Indication for manual operation (option)	Indication whether manual operation is active/not active via single switch (1 change-over contact)
Electrical connection	Standard: AUMA Ex plug/socket connector (KT); screw-type motor terminals; control terminals in spring clamp terminal technology
	Option: AUMA Ex plug/socket connector with terminal blocks (KES)
Threads for cable entries	Standard: Metric threads
	Option: Pg threads, NPT threads, G threads
Terminal plan	TPA00R2AA-001-000 (basic version)
Valve attachment	Standard: B1 according to EN ISO 5210
	A, B2, B3, B4, C, D according to EN ISO 5210
	Options: A, B, D, E according to DIN 3210
	C according to DIN 3338
	Special valve attachments: AF, AK, AG, B3D, ED, DD, IB1, IB3
	A prepared for permanent lubrication of stem

Table 1: 3-phase AC standard voltages

Voltages/frequencies											
Volt [3~]	220	230	380	380	400	400	415	440	460	480	500
Hz	60	50	50	60	50	60	50	60	60	60	50

Table 2: 3-phase AC special voltages

Voltages/frequencies								
Volt [3~]	220	440	525	575	600	660	690	
Hz	50	50	50	50	60	50	50	

Electromechanical control unit	
Limit switching	Counter gear mechanism for end positions OPEN and CLOSED
	Turns per stroke: 2 to 500 (standard) or 2 to 5,000 (option)
	Standard: Single switch (1 NC and 1 NO) for each end position, not galvanically isolated
	Options: Tandem switch (2 NC and 2 NO) for each end position, switch galvanically isolated Triple switch (3 NC and 3 NO) for each end position, switch galvanically isolated Intermediate position switches (DUO limit switching), adjustable for each direction of operation
Torque switching	Torque switching adjustable for directions OPEN and CLOSE
	Standard: Single switch (1 NC and 1 NO) for each direction, not galvanically isolated
	Option: Tandem switch (2 NC and 2 NO) for each direction, switch galvanically isolated
Switch contact materials	Standard: Silver (Ag)
	Option: Gold (Au), recommended for low voltage actuator controls
Position feedback signal, analogue (options)	Potentiometer or 0/4 – 20mA (electronic position transmitter)
Mechanical position indicator (option)	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED
Running indication (option)	Blinker transmitter
Heater in switch compartment	Standard: Self-regulating PTC heater, 5 – 20 W, 110 – 250 V AC/DC
	Options: 24 – 48 V AC/DC or 380 – 400 V AC
	A resistance type heater of 5 W, 24 V AC is installed in the actuator in combination with AMExC or ACExC actuator controls.

Electronic control unit (option, only in combination with ACExC actuator controls)	
Non-intrusive settings	Magnetic limit and torque transmitter (MWG)
	Turns per stroke: 2 to 500 (standard) or 10 to 5,000 (option)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Mechanical position indicator (option)	Continuous self-adjusting indication with symbols OPEN and CLOSED
Running indication	Blinking signal via actuator controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC

Service conditions	
Use	Indoor and outdoor use permissible

Service conditions	
Mounting position	Any position
Installation altitude	≤ 2,000 m above sea level > 2,000 m above sea level on request
Ambient temperature	Standard: –30 °C to +40 °C/+60 °C Options: –40 °C to +40 °C/+60 °C –60 °C to +40 °C/+60 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range
Enclosure protection in accordance with IEC 60529	IP68 with AUMA 3-phase AC motor Terminal compartment additionally sealed against interior of actuator (double sealed) According to AUMA definition, enclosure protection IP68 meets the following requirements: • Depth of water: maximum 8 m head of water • Continuous immersion in water: maximal 96 hours • Up to 10 operations during immersion • Modulating duty is not possible during immersion.
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)
Vibration resistance according to IEC 60068-2-6	2 g, 10 to 200 Hz (AUMA NORM), 1 g, 10 to 200 Hz (for actuators with AMExC or ACExC actuator controls) Resistant to vibration during start-up or for failures of the plant. Valid for multi-turn actuators-turn actuators in version AUMA NORM and in version with actuator controls, each with AUMA plug/socket connector. Not valid in combination with gearboxes.
Corrosion protection	Standard: KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution. Options: KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution. KX-G: Same as KX, however aluminium-free version (outer parts)
Coating	Double layer powder coating Two-component iron-mica combination
Colour	Standard: AUMA silver-grey (similar to RAL 7037) Option: Available colours on request
Lifetime	AUMA multi-turn actuators meet or exceed the lifetime requirements of EN ISO 22153. Detailed information can be provided on request.
Sound pressure level	< 72 dB (A)
Further information	
EU Directives	ATEX Directive 2014/34/EU Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU
Reference documents	Dimensions SAREx 07.2 – SAREx 16.2/SAREx 07.2 – SAREx 16.2 Electrical data SAREx 07.2 – SAREx 16.2